



SPECIFICATION		
Model NO.	LBH30HTC500FK	LBH30THC500FK
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps; CVI: 4M@30fps, 2M@30fps	
Camera		
Image Sensor	1/2.5" CMOS Sensor	
Image Resolution	5MP	
Effective Pixels	5M:2592*1944 4M:2560*1440	
TV System	PAL/NTSC	
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s	
S/N Ratio	≥50dB	
Scanning System	Progressive Scan	
Lens		
Focus Length	3.6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Pixels	6M Pixels	
Auto Iris Support	NO	
Night Vision		
Infrared LED	14μ x 20PCS	
Infrared Distance	25M	
IR Status	Under 10 Lux by CDS	
IR Power On	CDS Auto Control	
Camera Features		
Starlight	/	
Day/Night	YES	
OSD Menu Language	YES	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
Noise Reduction	DNR	
Picture Adjustment	YES	
WDR	YES	
OSD Support	YES	
UTC	YES	
Dip Switch	/	
General		
Housing	Metal, IP66	
Bracket	YES	
Dual Voltage	NO	
IR Cut Filter	YES	
Heater	NO	
Audio	/	
Operation Temperature	-10℃ ~ +50℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 600mA	
Dimension	157(W) x 70(H) x 66(D)mm	
Weight	650g	