

Longse



| SPECIFICATION         |                                      |                         |                         |
|-----------------------|--------------------------------------|-------------------------|-------------------------|
| Model NO.             | LIRDQHTC200FS                        | LIRDQCHT200FS           | LIRDQTHC200FS           |
| Video Output Mode     | AHD/CVI/TVI/CVBS 4 IN 1              | CVI/AHD/TVI/CVBS 4 IN 1 | TVI/AHD/CVI/CVBS 4 IN 1 |
| Camera                |                                      |                         |                         |
| Image Sensor          | 1/2.9" SONY 2.1MP CMOS Sensor        |                         |                         |
| Image Resolution      | 2MP 1080P/ 960H                      |                         |                         |
| Effective Pixels      | 1920*1080                            |                         |                         |
| TV System             | PAL/NTSC                             |                         |                         |
| Electronic Shutter    | 1/25s~1/50,000s , 1/30s~1/60,000s    |                         |                         |
| S/N Ratio             | ≥50dB                                |                         |                         |
| Scanning System       | Progressive Scan                     |                         |                         |
| Lens                  |                                      |                         |                         |
| Focus Length          | 2.8-12mm                             |                         |                         |
| Focus Control         | Manual                               |                         |                         |
| Lens Type             | Varifocal                            |                         |                         |
| Pixels                | 2M Pixels                            |                         |                         |
| Auto Iris Support     | NO                                   |                         |                         |
| Night Vision          |                                      |                         |                         |
| Infrared LED          | 14μ x 24PCS                          |                         |                         |
| Infrared Distance     | 30M                                  |                         |                         |
| IR Status             | Under 10 Lux by CDS                  |                         |                         |
| IR Power On           | CDS Auto Control                     |                         |                         |
| Camera Features       |                                      |                         |                         |
| Starlight             | /                                    |                         |                         |
| Day/Night             | YES                                  |                         |                         |
| OSD Menu Language     | YES                                  |                         |                         |
| White Balance         | AUTO / MANUAL                        |                         |                         |
| Gain Control          | AUTO                                 |                         |                         |
| Noise Reduction       | 3DNR                                 |                         |                         |
| Picture Adjustment    | YES                                  |                         |                         |
| WDR                   | YES                                  |                         |                         |
| OSD Support           | YES                                  |                         |                         |
| UTC                   | YES                                  |                         |                         |
| Dip Switch            | /                                    |                         |                         |
| General               |                                      |                         |                         |
| Housing               | Ball Part Metal, Other Plastic, IP66 |                         |                         |
| Bracket               | NO                                   |                         |                         |
| Dual Voltage          | NO                                   |                         |                         |
| IR Cut Filter         | YES                                  |                         |                         |
| Heater                | NO                                   |                         |                         |
| Audio                 | /                                    |                         |                         |
| Operation Temperature | -10℃ ~ +50℃ RH95% Max                |                         |                         |
| Storage Temperature   | -20℃ ~ +60℃ RH95% Max                |                         |                         |
| Power Source          | DC12V±10%, 800mA                     |                         |                         |
| Dimension             | Φ 120 x 104(H) mm                    |                         |                         |
| Weight                | 600g                                 |                         |                         |